

# Stock Mini Car Rules & Regulations

*\* Inspection is on September 7th 12-330 p.m.*

*\*Derby begins at 4pm.*

*\*Payout: 19 cars or less= 1st \$2000, 2nd \$700, & 3rd \$300.*

*20 cars or more= 1st \$2500, 2nd \$900, & 3rd \$600.*

If not listed below it is not approved nor allowed

NO TOLERANCE: If you have a question contact us.

## Cheap Man's Build:

- 1) Wheelbase is RWD 106" FWD 108".
- 2) 10" bumper shock (2x2 Maximum tubing). Any OEM front bumper shock (with 10" of weld per shock to frame, 10" on top, 10" on bottom). No rear brackets on front.
- 3) Cage must be 5" off of the floor and cannot be touching the firewall before or after the derby.
- 4) Maximum of four points cage (4x4x1/4" size maximum). Cage can be no more than 8" behind front door seam. Gas tank protector made out of 2x2 tubing, 3" away from packaging tray.
- 5) May take front two body or core support pucks out and bolt solid with 3/4" all thread and may go through core support and hood. Rear body bolts of cradle must remain stock, no welding together.
- 6) Maximum Tire Size: 15 INCHES, small center and may have multiple lugs. No solid tires. No built rims.
- 7) Maximum six cyl. No V8's.
- 8) Doors may be welded, 6 on 6 ft.
- 9) Trunk may be tucked up to 50% . No wedges. No welding on trunk/trunk lid.
- 10) Speaker deck must remain in the factory position. Do not canoe or V your trunk.
- 11) No creasing or bending of body.
- 12) No plating on frame, unless preran. Two 3x3x1/4" patch plates per frame rail, showing visible damage.

- 13) Windshield bar maximum 2x1/4". Strap may have rear window bar, but cannot be attached to the cage; it must be bolted to the back of the roof and to the speaker deck.
- 14) May run loaded bumper and may use full size bumper, however, is not allowed to be loaded or welded, and must be cut down to the width of the car. No homemade or aftermarket bumpers.
- 15) No aftermarket or self-built suspension. Suspension parts must remain stock.
- 16) Must have two 4" holes in the hood and trunk lid (inspectors may be able to see into the trunk).
- 17) No skid plates or protectors.
- 18) No leaf or coil conversions.
- 19) Aftermarket gas or brake shifters are allowed.
- 20) Floating Gas Tank protector allowed.
- 21) May use tubing, maximum of 2x2x1/4". No further than 3" away from tank in every direction.
- 22) Two downtubes on the driver's side. No kickers or downtubes anywhere else (from center of door to where the dash meets door bar, maximum of 2x2 tubing).

FOR QUESTIONS: 217-690-7610

**THESE ARE THE FINAL RULES & REGULATIONS. No grey areas! Safety is our top priority!**