

SALINAS VALLEY FAIR FARMER 500

Pit Gates Open 2 PM – 6 PM for Driver Check-In

Race Time 7:30 PM

ENTRY FORM

DRIVER'S NAME: _____ CAR # _____

DRIVER'S LICENSE # _____ AGE: _____

ADDRESS: _____

CITY: _____ ST: _____ ZIP: _____

CELL: _____ EMAIL: _____

CAR MAKE: _____ MODEL: _____ YEAR: _____

SPONSORS: _____ SPONSOR: _____

SPONSORS: _____ SPONSOR: _____

**DRIVERS MUST BE OVER 21 YEARS OF AGE TO PARTICIPATE IN EVENT AND
MUST HAVE A VALID DRIVER'S LICENSE ON DAY OF DERBY.**

Pit Gates Open 2 PM – 6 PM for Driver Check-In

Race Time 7:30 PM

**CARS MAY NOT BE PAINTED WITH ANY VULGAR OR DRUG RELATED SIGNS, PICTURES, OR WORDS
NO ALCOHOL OR WEAPONS ALLOWED IN PIT AREA**

PIT CREW: MUST BE OVER 18 YEARS OF AGE. NO ONE UNDER THE AGE OF 18 ALLOWED IN PIT AREA

#1 _____

#2 _____

#3 _____

#4 _____

DRIVER'S SIGNATURE: _____ DATE: _____

SUBMIT ENTRY FORM BY MAY 4, 2019

PLEASE E-MAIL DERBY ENTRY FORM TO SVF@SalinasValleyFair.com

OR MAIL TO SALINAS VALLEY FAIR, 625 DIVISION STREET, KING CITY, CA 93930

QUESTIONS? CALL/TEXT MITCH MOSS 831-212-8388

"FARMER 500" FLAT TRACK EXTREME RACE RULES

- 1. This is not a destruction derby, you will be disqualified for intentional or excessive hits or ramming of another car.**
2. 12 inch high up right numbers mounted on roof and must be visible from all 4 directions.
3. All glass, chrome, fiberglass, rubber, plastic, fuel tanks, door handles, mirrors, bumper tips, stripping, and all flammable materials must be removed. (anything other than glass removed). **All cars must have window net on Driver side**
4. Bodies: Must be relatively straight, look sharp, no trimming of the fender wells before heats. No welding anywhere except outside of doors for safety. No bolting anywhere. No bracing or reinforcing, cement, stock only.
5. All doors must be welded with #5 rebar or 1" x ¼" strap steel.
6. Box framed cage to driver and front passenger side (to protect driver and components.) Inside of front doors can be plated. Plates can go back 18" from the back of the driver's seat.
7. Driver must have (2) two 3" x ¼" vertical straps or #5 re-bar in stock windshield and rear window positions.
8. Fuel cell can be (5) five gallons MAX and Must be metal. Must be located on the center of the rear passenger area. Must be covered and secured with a manual shut off valve. Electric fuel pump can be used with an electric kill switch. Kill switch must be located on top of dash by driver A pillar. Must be a push/pull switch and must be off in the down position. Switch area must be painted red.
9. Diagonal bars from rear of driver and passenger 3" tube bracket to support to rear passenger seat area at lower floor pans. Maximum of (2) two bars.
10. No welding the trunk or hood. Trunk lid must be secure with 4 chains no more than 12" from rear of trunk lid.
11. 4 chains maximum. Chain must be bolted to itself and looped around the bumper. ½" Coil Chain max. No overlap. Chains can be no more than 12" from front of hood. No welding chain to frame.
12. No extra support to bumpers. If 5mph bumper, shock can be welded. Bumper tip may be trimmed. No welding to frame.
13. Engine swap ok, but in stock original location. Mounts in stock position 2 and head mounts allowed from head to frame within the length of the valve cover. Must be straight down, no forward or rearward angles. Maximum ¼" thick 4" wide strap. Only allowed one mount each side of engine-head mount.
14. Radiator must be in original stock position, No additional radiator supports or mounts. Wire can be used. No water inside the vehicle.
15. No solid Tires. No chains on tires, Tires must be D.O.T. approved.
16. Battery must be secured and covered. Must be in passenger compartment.
- 17. Drivers side 4 point seat belt must be in working condition.**
18. Maximum vehicle height of 26" from the ground to top of the bumper. No spring spacers allowed.
19. Only the driver will be allowed to speak to the officials regarding the derby. Absolutely NO pit crew member or family or fan will be acknowledged.
20. Frames: Stock only! No welding bracing or reinforcement. All cars must be 4 cylinder stock car with 4 cylinder stock engine.
21. Trans Coolers: Optional must be securely mounted in the drivers compartment. Lines and cooler must be covered and sealed to protect against fire. Safety First! Ice Ok.
22. Body of frame hardware: STOCK ONLY. Do not alter in any way, only OEM.
- 23. All Cars must have a secured fire extinguisher where driver can easily reach.**

Pit Gates Open 2 PM – 6 PM for Driver Check-In

Race Time 7:30 PM