

6500# Big Block and Small Block Hot Street Rules

- ***MUST BE STREET LEGAL, LICENSED AND INSURED***
- ***Any year full size steel OEM body and frame. NO stripping of truck in anyway. Wheel,wells,interior,doors,glass must be intact.***
- ***No bigger than 1 ton drive train, NO pro fab cases.***
- ***NO electric water pumps. Must have alternator***
- ***Must have factory style steering setup. NO electric over hydro steering.***
- ***Naturally aspirated single carb only. NO dominators, nitrous, or whiffers.***
- ***Factory produced cast iron block. NO aluminum heads unless OEM***
- ***Vehicle MUST HAVE ALL FUNCTIONING BRAKES! No stripping of components!***
- ***Fuel cells OK if secured in the bed. No dry sumps, air pumps***
- ***Headers allowed, down swept with DOT approved mufflers to exit behind cab.***
- ***NO floating hitches. Rigid in all directions. Farthest point of draw bar style hitch not to exceed the top of OEM frame rail and no farther forward than center of rear axle.***
- ***26" hitch height. Minimum 3" opening to extend beyond furthest point of body. NO REACHING UNDER TRUCKS TO HOOK!***
- ***NO SOLID SUSPENSIONS! NO STOP BLOCKS OF ANY KIND!***
- ***SFI approved bell housing or blanket and flywheel is recommended! Fire extinguisher is also recommended.***
- ***No hanging weight. In box or cab is OK. No weighted bumpers.***
- ***35" MAX DOT APPROVED TIRES. NO CUT TIRES! Siping is OK***

Open Diesel Class

The open Diesel Class is designed to be a fun “run what you bring” class with an unlimited amount of performance upgrades.

Weight: 8500 lbs

Hitch Height: 26”

Single or twin turbocharger is allowed.

Safety equipment STRONGLY recommended

***Kill switch and/or air shut off**

***U-joint Shields and driveshaft loops**

***Fire jacket and helmet**

***Fire extinguisher**

Front hanging weight is allowed not to exceed 60” from center of front axle.

Weights allowed in bed. No weights allowed in cab.

Nitrous, Propane, water meth are allowed. All bottles must be properly secured.

Solid Suspension is allowed.

Reese style hitch or draw-bar style hitch allowed. 26” hitch height.

Exhaust must exit the truck in any vertical form. Hood stacks are allowed.

Pulling tires and cut tires allowed not to exceed 35x12.50.